**Bugatti Super Sport (2011) GENERAL** Length 4462 mm Width 1998 mm Height (normal position) 1190 mm Wheelbase 2710 mm Curb weight 1838 kg Max. permitted laden weight 2200 kg Tank capacity 100 I **DRIVE TRAIN** Motor Type / Number of Cylinders W16 7993 cm<sup>3</sup> Cylinder capacity Power output 882 KW (1200 hp) at 6400 rpm Max. torque 1500 Nm at 3000-5000 rpm 86 mm Bore Stroke 86 mm Compression ratio 8,3:1 7 Gear DSG Gearbox Allwheels Drive Front axle differential with Haldex clutch Power distribution Rear axle with transverse differential lock SUSPENSION Wheel suspension Double wishbone front / rear Max. weight per axle 990 / 1210 front / rear (kg) Tyres, front 265-680 ZR 500A Tyres, rear 365-710 ZR 540A 3.0 bar front Tyre pressure 3.0 bar rear SUSPENSION HEIGHT Standard 115 / 115 front / rear (mm) Handling 80 / 95 front / rear (mm) Top speed 65 / 70 front / rear (mm) **BRAKES** 400 mm front Brake disc diameter 380 mm rear Brake disc material front/rear Ceramics Number of wheel brake cylinders 8 front 6 rear Number of brake pads 4 front 2 rear PERFORMANCE Top speed 415 km/h Acceleration 2.5 sec 0-100 km/h 6.7 sec 0-200 km/h 14.6 sec 0-300 km/h 9.7 sec 1/4 Mile 23.6 sec 1 Mile Lateral acceleration 1.4 g Braking distance 31.4 m 100-0 km/h Accelerating and Braking 5.9 sec 0-100-0 km/h 12.5 sec 0-200-0 km/h 22.5 sec 0-300-0 km/h 9.2 sec 0-100-0 mph 25.6 sec 0-200-0 mph Gearbox shift time 0.1 sec FUEL CONSUMPTION\* 37.21 Urban Extra-Urban 14.91 23.1 I Combined CO<sub>2</sub> EMISSION 867 g/km In town 348 g/km Extra-Urban 539 g/km Combined Fuel type Super lead free 98 RON/ROZ **AERODYNAMICS CW-VALUE** Standard 0.388 0.471 Handling 0.348 Topspeed Airbrake 0.695 WING / SPOILER ANGLE Standard Retracted / 6° cool-down position 18° / 27° Handling 3° Top speed Brake setting 55° / 27° Special features Central hydraulics / Double diffusor THREE SUSPENSION HEIGHTS For town traffic and speeds of up to 180 km/h. From STANDARD 180 km/h, automatic configuration switches from Standard to Handling (Flaps in front diffusers open) HANDLING For open roads and highways or manually selectable for race tracks (Flaps in front diffusers open) For very high-speed driving (over 375 km/h), manually TOPSPEED selectable with separate key. (Flaps in front diffusers closed)

myAutoWorld.com

\* As measured by EC Directives 1999/94/EG