SPECIFICATIONS

Technical Specifications

2013 Audi RS 5 Cabriolet

Engineering/ Performance	RS 5 Cabriolet
Engine	Eight-cylinder
Arrangement	Front mounted- longitudinal
Bore (in)	3.33 (84.5 mm)
Stroke (in)	3.65 (92.8 mm)
Displacement (cu in)	254 (4163 cc)
Compression Ratio	12.5:1
Horsepower @ rpm	450 @ 8250 (331 kw)
Torque (lb-ft @ rpm)	317 @ 4000 (430 nm
Induction/ Fuel injection	FSI®
quattro® S tronic® (0-60 mph)	4.9
Top track speed (electronically limited)* (mph)	174 (280 km/h)

Transmission/ Drivetrain

Exterior measurements

Headroom sunshade (front / rear) (in)

Legroom (front / rear) (in)

Wheelbase (in)

Multitronic® FWD CVT

Cylinder block	Aluminum alloy
Cylinder head	Aluminum alloy
Firing order	1-5-4-8-6-7-2
Valvetrain/ Intake	DOHC, four valves per cylinder, hydraulic adjustment
Supercharger/ Turbocharger	
Max boost	
Emissions	Tier2 BIN5 / ULEV II
Start-stop efficiency system	

RS 5 Cabriolet Body/ Suspension Five-link front suspension with stabilizer bar

Sport suspension calibration	
S5 sport suspension calibration	
Adaptive dampening suspension	
RS 5 sport suspension calibration	-
Electromechanical power steering system	-
Sports differential	-
Ventilated front disc/ solid rear disc brakes (in)	
Ventilated front disc/ ventilated solid rear disc brakes (in)	14.4 / 12.8 (365 / 324 mm)
Ceramic front brakes	15.0 (380 mm)

Six-speed manual transmission with Audi quattro® all-wheel drive (Coupe/ Cabriolet)	
Eight-speed Tiptronic® automatic transmission with Audi quattro® all-wheel drive (Coupe/ Cabriolet)	
Seven-speed Audi S tronic® duel-clutch transmission with Audi quattro® all-wheel drive (Coupe/ Cabriolet)	
Gear ratio:	S tronic
1st	3.692: 1
2nd	2.238: 1
3rd 4th 5th 6th 7th 8th Reverse Final drive	1.559: 1
	1.175: 1
	0.915: 1
	0.745: 1
	0.617: 1
	2.944:1

Length (in) 183.0 (4649 mm) Height (in) 54.3 (1380 mm) 73.2 (1860 mm) Width (in) w/ mirrors 79.5 (2020 mm) 62.4 / 62.3 Track (in) front / rear (1586 / 1582 mm) Curb weight (lb) 4420 Weight distribution Not disclosed Ground clearance (loaded) Not disclosed Drag coefficient 0.34

RS 5 Cabriolet

108.3 (2751 mm)

(1016 / 923 mm)

NA

41.3 / 31.9

(1049 / 810 mm)

54.2 / 46.8

13.4

RS 5 Cabriolet

Electromechanical,

speed sensitive power

rack & pinion

14 Volts - 190 amp

Four-year/ 50,000 mile

new vehicle limited

warranty

0000

Interior measurements 40.0 / 36.3 Headroom (front / rear) (in)

Shoulder room (front / rear) (in) (1378 / 1190 mm) Luggage capacity (cu ft)

Luggage capacity (2nd row folded) (cu ft)		
Seating capacity	4	
EPA mileage estimates*/ Capacities		
Multitronic® transmission (City / Highway / Combined)*		
Tiptronic® automatic transmission (City / Highway / Combined)*		
S tronic® automatic transmission (City / Highway / Combined)*	16/22/18	
Engine oil (qt)	11.3 (10.7 liter)	

Coolant system (qt) Fuel (gal) 16.1 (61 liter) Recommended fuel Premium unleaded * See www.fueleconomy.gov for EPA estimates. Your mileage with vary.

Type

Ratio	15.9:1
Turning circle (curb-to-curb) (ft)	38.1 (11.6 m)
Electrical system	
Liectificat System	

Warranty/ Maintenance


Steering

Alternator

		Twelve-month/ 5,000 mile (whichever occurs first NO CHARGE first scheduled maintenance
	= Standard	
	= Optional	
-	= Not Available	

DIMENSIONS

2013 Audi RS 5 Cabriolet



1 Shoulder width

² Elbow width * Maximum headroom Dimensions in inches Dimensions of vehicle unloaded